	Project Name:			AIA#:	
Model #:		Location:			
-			_		



Countertop Induction Range

Energy efficient cooking

No open flames, portable, light weight, and stores away easily.







Model

□ GIR18

Standard Features

- 1800W, 120V
- 7 power levels
- Touch pad controls and 4 digit LED display
- Digital timer
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable feet for leveling unit
- Attached 5½-foot power cord and NEMA 5-15P plug
- Seamless stainless steel construction
- Durable ceramic cooktop
- Easy-to-clean controls and cooktop

Warranty

One year parts and labor

Applications

Omelets, eggs & bacon, seafood, poultry, burgers, delicate sauces, butter, chocolate, etc.

To select options see back

Approved by:	Date:



For Indoor Use Only

SPECIFICATIONS

- Seamless stainless steel construction
- Touch pad controls and 4 digit LED display
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable foot for leveling unit
- Attached 5½-foot power cord and plug

Model	Power Levels	Temp Settings	Cooking Surface	Electric	AMPs	Wattage	NEMA Plug Type
GIR18	7	140°F-460°F	4.75" to 10.25"	120V/60Hz	15	1800 W	5-15P (U.S.) 😲

IMPORTANT: PERSONS WITH PACEMAKERS

Persons with pacemakers should stay at least 3 feet away from the induction range.

When using the induction range with the general public, a pacemaker notice should be posted near the equipment in use.

STANDARD EQUIPMENT:

Auto pan detection: Range detects if proper cookware/pan is placed on cooktop.

Automatic shut-off: Automatically shuts off when timer runs to "0".

Over-heat protection: Unit senses when the pan overheats and when the electrical components overheat; the unit then shuts

Digital timer: Set timer from 0-180 minutes.

Bright LED display: Bright 4 digit LED display for easy viewing.

Suitable Pans:

Steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10.25".

DIMENSIONS & SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of reinforced carton are listed below and may vary from shipment to shipment.

Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
GIR18	16.75" L × 13" W × 4" H	12.46 lbs.	19" L × 15.25" W× 6" H	15 lbs.
	(42.54 cm × 33 cm × 10.16 cm)	(5.65 kg)	(48.26 cm × 38.73 cm × 15.2 cm)	(6.8 kg)

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodeguip.com